



Geberit Sigma concealed cistern 8 cm, 6 / 3 litres







Application purposes

- · For masonry walls
- For installation in part- or room-height prewall installations
- · For installation in room-height installation walls
- · For floor-standing WCs
- · For single flush, dual flush or stop-and-go flush

Characteristics

- Series 2016
- Concealed cistern with front actuation
- Concealed cistern fully insulated against condensation
- · Pre-mounted direct plastering netting
- · Immediate post flush possible with factory setting
- · Flush bend fitted
- Flush bend adjustable 2 cm upwards and 1 cm downwards
- Tool-free installation and maintenance work on concealed cistern
- · Water supply connection on the top, offset to left side
- · Protection box for service opening can be cut to length, suitable for surface-even actuator plates

Technical data

Flow pressure	0.1–10 bar
Flush volume, factory setting	6 and 3 l
Flush volume large, adjustment range	4.5 / 6 / 7.5
Flush volume small, adjustment range	3–4

Scope of delivery

- Water supply connection R 1/2", compatible with MeplaFix, with integrated angle stop valve and hand wheel
- Protection box for service opening
- Flush bend with recess shells
- Flush bend extension, ø 45 mm
- · Protection plug
- · 2 slotted flat irons
- · Fastening material

Article

Art. no.

109.791.00.1

Actuator plate has to be ordered separately