



## Geberit Duofix element for wall-hung WC, 112 cm, with Sigma concealed cistern 12 cm, corner construction



### Application purposes

- For drywall construction
- For installation in part- or room-height prewall installations
- For free-standing installation with wall fixation on one side
- For wall-hung WCs with connection dimensions in accordance with EN 33:2011
- For wall-hung WCs with projection up to 62 cm
- For single flush, dual flush or stop-and-go flush
- For floor constructions 0–20 cm

### Characteristics

- Self-supporting frame, powder-coated
- Variable wall fixture 30°–60°, can be pulled out 10 cm on both sides
- Integrated panelling support extendible at front, top and left/right
- Minimum and maximum dimensions for floor area: W = 56 / 76 cm, D = 28 / 38 cm, leg length = 39.6 / 53.7 cm
- Frame suitable for ceramic WC appliances with small contact surface (with pressure-resistant wall covering)
- Galvanized feet
- Feet adjustable 0–20 cm
- Leg support not on the perimeter for lateral offset of discharge pipe
- Straight connector can be mounted without tools
- Fastening for straight connector, sound-absorbing
- Concealed cistern with front actuation
- Concealed cistern fully insulated against condensation
- Immediate post flush possible with factory setting
- Tool-free installation and maintenance work on concealed cistern
- Water supply connection on the rear or top centre
- Protection box for service opening can be cut to length
- Equipped with conduit pipe for feed pipe for connection of Geberit AquaClean shower toilets
- With fastening option for electrical connection

### Technical data

Flow pressure	0.1–10 bar
Flush volume, factory setting	6 and 3 l
Flush volume large, adjustment range	4.5 / 6 / 7.5 l
Flush volume small, adjustment range	3–4 l


## Scope of delivery

- Water supply connection R 1/2", compatible with MeplaFix, with integrated angle stop valve and hand wheel
- Protection box for service opening
- Connection set for WC, Ø 90 mm
- Straight connector made of PE-HD, Ø 90 mm
- Adapter socket made of PE-HD, Ø 90 / 110 mm
- 2 protection plugs
- 2 threaded rods M12
- Concealed outlet for drilling hole Ø 68 mm, for electrical connection
- Fastening material
- Connection for single-side wall fixation

## Article

### Art. no.

**111.390.00.5**

-  Actuator plate has to be ordered separately

## Accessories

- Accessory overview: Geberit Duofix elements for WCs